



Large Displays

Models: DIS-6i, DIS-4i

- 4 large digits 16 cm (DIS-6i) and 10 cm (DIS-4i) height, visible from 120° angle.
- Input from 4..20 mA, thermocouples, volts, pulses, etc
- 5 years guarantee.

General Description

This large size display can be seen from far away, helping work coordination by maintaining the plant personnel informed of variables such as production record, temperature, weight, etc..
They work as a id20 indicator repeater. The id20 panel meter is placed inside the display. This way is possible to have the inputs of the id20, e.g. voltages, currents, thermocouples, Pt100, rate meters, etc.

Technical Specifications.

Input :	Inside is placed a id20 family panel meter, e.g. id20-bas, id20-vac, id20-tac. Allows to program and scale several analog input types. By example counts, temperatures, 4...20 mA, volts, etc.		
Display	4 digits, 7 segments each		
	Digits dimension	DIS-6i: 16 cm H x 11 cm W (one digit). DIS-4i: 10 cm H x 6 cm W (one digit).	51cm W (4 digits) 33cm W (4 digits)
	Brightness:	300 mcd min., 120° angle visibility.	
Power Supply	200...275 Vac y 100...137 Vac, 45...65 Hz. DIS-6i: 40 W max. DIS-4i: 25 W max.		
Construction:	Aluminum and Polycarbonate		
	Dimensions and Weight	DIS-6i: 28 cm H x 61 cm W x 12 cm D, DIS-4i: 20 cm H x 42 cm, W x 12 cm D,	8kg max 4kg max.
	Operating temperature	0 ... 50 °C.	

PART CODES:

Model:		
	DIS-6i	16 cm (6 inch) 4 digit display
	DIS-4i	10 cm (4 inch) 4 digit display

FOR MORE INFORMATION:

ARIAN S. A.
El Comendador 2340
Santiago, Chile
Fono/Fax 4218333
arian@arian.cl
<http://www.arian.cl/>